




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A61M 25/09		A1	(11) International Publication Number: WO 00/40288
			(43) International Publication Date: 13 July 2000 (13.07.00)
(21) International Application Number: PCT/US99/30771 (22) International Filing Date: 21 December 1999 (21.12.99) (30) Priority Data: 09/224,451 31 December 1998 (31.12.98) US (71) Applicant: ADVANCED CARDIOVASCULAR SYSTEMS, INC. [US/US]; 3200 Lakeside Drive, P.O. Box 58167, Santa Clara, CA 95052-8167 (US). (72) Inventors: JAFARI, Mo; 40132 Zamura Court, Murrieta, CA 92129 (US). FARIABI, Sepehr; 44241 Topaz Court, Fremont, CA 94539 (US). BRENNAN, Lawrence, E.; 43652 Ortona Street, Temecula, CA 92592 (US). CORNISH, Wayne, E.; 1650 Scooter Lane, Fallbrook, CA 92028 (US). JALISI, Marc, M.; 30660 Milky Way Drive #J-76, Temecula, CA 92592 (US). ANDERSON, David, M.; 45531 Clubhouse Drive, Temecula, CA 92592 (US). (74) Agents: CHOW, Y., Ping et al.; 525 University Avenue, Palo Alto, CA 94301-1900 (US).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: GUIDEWIRE WITH SMOOTHLY TAPERED SEGMENT



(57) Abstract

A guidewire for intraluminal advancement of a medical device within a patient which has an elongate core member with a flexible body member disposed on a distal section thereof. In one embodiment, the distal section of the elongate core member has at least one flexible segment with at least one pair of opposed tapered or parallel faces. Preferably the flexible segment with the tapered or parallel faces is disposed at the distal end of the elongate core and forms a shapable segment.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

GUIDEWIRE WITH SMOOTHLY TAPERED SEGMENT

BACKGROUND OF THE INVENTION

5 This invention relates to the field of guidewires for advancing intraluminal devices such as stent delivery catheters, balloon dilatation catheters, atherectomy catheters and the like within body lumens.

10 In a typical percutaneous coronary procedure, a guiding catheter having a pre-formed distal tip is percutaneously introduced into a patient's peripheral artery, e.g. femoral or brachial artery, by means of a conventional Seldinger technique and advanced therein until the distal tip of the guiding catheter is seated in the ostium of a desired coronary artery. A guidewire is first advanced by itself through the guiding catheter until the distal tip of the guidewire extends beyond the arterial location where the procedure is to be performed. Then a rail type catheter, such as described in U.S. Patent No. 15 5,061,395 (Yock) and the previously discussed McInnes, et al., is mounted onto the proximal portion of the guidewire which extends out of the proximal end of the guiding catheter which is outside of the patient. The catheter is advanced over the guidewire, while the position of the guidewire is fixed, until the operative means on the rail type catheter is disposed within the 20 arterial location where the procedure is to be performed. After the procedure the intravascular device may be withdrawn from the patient over the guidewire or the guidewire repositioned within the coronary anatomy for an additional procedure.

25 A guidewire may also be used in conjunction with the delivery of an intracoronary stent. One method and system involves disposing a compressed or otherwise small diameter stent about an expandable member such as a balloon on the distal end of a catheter, advancing the catheter through the patient's vascular system over a guidewire until the stent is in the desired location within a blood vessel and then expanding the 30 expandable member on the catheter to expand the stent within the blood vessel. The dilated expandable member is then contracted and the catheter

withdrawn, leaving the expanded stent within the blood vessel, holding the passageway thereof open. This latter method and system can be used concurrently with balloon angioplasty or subsequent thereto.

5 Further details of guidewires, and devices associated therewith for various interventional procedures can be found in U.S. Patent No. 4,748,986 (Morrison et al.); U.S. Patent No. 4,538,622 (Samson et al.); U.S. Patent No. 5,135,503 (Abrams); U.S. Patent No. 5,341,818 (Abrams et al.); and U.S. Patent No. 5,345,945 (Hodgson, et al.) which are hereby incorporated herein in their entirety by reference thereto.

10 Conventional guidewires for angioplasty, stent delivery, atherectomy and other intravascular procedures usually comprise an elongate core member with one or more tapered segments near the distal end thereof. A flexible body member, such as a helical coil or a tubular body of polymeric material, is typically disposed about the distal portion of the core member.
15 A shapable member, which may be the distal extremity of the core member or a separate shapeable ribbon which is secured to the distal extremity of the core member extends through the flexible body and is secured to the distal end of the flexible body by soldering, brazing or welding, or an adhesive in the case of polymeric flexible bodies which forms a rounded distal tip. The
20 leading tip is highly flexible and will not damage or perforate the vessel and the portion behind the distal tip is increasingly stiff which better supports a balloon catheter or similar device.

The shapeable member or ribbon of a typical guidewire is a small diameter wire which has been flattened to a constant transverse profile.
25 Flattening of the shapable member facilitates the shapability of the member, however, a shapable member having a constant transverse profile or flexibility can be subject to prolapse during use. Prolapse occurs when the shapable member gets bent back on itself in a constrained lumen and is difficult to straighten out with proximal manipulation. One method of
30 preventing prolapse or reducing the occurrence thereof is to have increased stiffness at a proximal end of a shapable member. This has been done with

incremental steps in the shapable member with thinner more flexible steps distally creating greater flexibility distally. However, the use of incremental steps can cause abrupt changes in flexibility of the shapable member which can be detrimental to smooth tracking and performance of the guidewire.

5 What has been needed is a guidewire with a shapeable member at the distal section that is continuously varied in flexibility and maintains a shapeable character. The present invention satisfies these and other needs.

SUMMARY OF THE INVENTION

10

The present invention is directed to a guidewire having an elongate core member with a proximal section and a distal section. The distal section preferably has at least one flexible segment with two or more opposed faces that are parallel or distally tapered in essentially the same or mirror image relationship to each other.

15 The distal section may also have one or more tapered segments which have typical distally decreasing tapers with substantially round transverse cross sections.

20

25

30

Preferably the flexible segment is disposed at a distal end of the distal section where it can perform the function of a shapeable member. The flexible segment has a length typically ranging from about 1 to about 12 cm, preferably about 2 to about 10 cm, although longer segments may be used. The flexible segment provides a controlled longitudinal variation and transition in flexibility of the core segment. A flexible body member having a proximal end and a distal end is typically disposed about and attached to the distal section of the elongate core member. A flexible body member, such as a helical coil, polymer jacket, or the like, surrounds and covers at least a portion of the distal section of the elongate core member. The proximal end of the helical coil or flexible body typically is secured to the distal section of the elongate core member. Depending on the selected lengths of the helical coil and the flexible segment or shapeable member, the junction of the proximal end of the coil to the core may be at an intermediate position on

the distal section or may be at an intermediate position on the flexible segment or anywhere in between.

5 In one preferred embodiment of a guidewire having features of the invention, the distal section of the core member has at least one flexible segment with at least two opposed tapered faces tapering distally over the length of the flexible segment to a smaller transverse separation. Optionally, the opposed tapered faces may be mirror images and parallel as well as distally tapered. In addition, the tapered faces may have either a substantially straight or curved longitudinal profile. Other than the flexible
10 segment, the construction of the guidewire is similar to the guidewire discussed above with a flexible body member disposed about at least a portion of the distal section and is secured thereto. The proximal section of the elongate core member is nominally round in cross section and preferably with a constant diameter and said round cross section preferably extends
15 distally to a proximal end of the flexible segment disposed on the distal section of the core. The flexible segment may be disposed anywhere on the distal section, but preferably is disposed at a distal end of the distal section, serving as a shapable member.

The taper geometry of the flexible segment may be modeled
20 mathematically. Specific taper or face angles or contours may be selected in keeping with the principles and spirit of the invention to achieve optimum performance for specific usage requirements. These and other advantages of the invention will become more apparent from the following detailed description of the invention when taken in conjunction with the
25 accompanying exemplary drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevation view, partially in section, of a guidewire embodying features of the invention.

30 FIG. 2 is an enlarged elevational view of a portion of the distal section of the elongated core member of the guidewire shown in FIG. 1.

FIG. 3 is an end view of the embodiment of FIG. 2, shown as viewed from line 3-3 in FIG. 2.

FIG. 4 is an elevational view of an elongated core member for a guidewire having features of the invention.

5 FIG. 5 is a side elevation view of the embodiment shown in FIG. 4.

FIG. 6 is a end view of the embodiment of FIGS. 4 and 5, shown as viewed from line 6-6 in FIG. 5.

FIG. 6A is a transverse cross sectional view of the flexible segment of FIG. 5 taken at lines 6A-6A.

10 FIG. 7 is an elevational view of a portion of an elongated core member for a guidewire having features of the invention.

FIG. 8 is a side elevation view of the embodiment of FIG. 7.

FIG. 9 is a end elevation view of the embodiment of FIGS. 7 and 8, shown as viewed from line 9-9 in FIG. 8.

15

DETAILED DESCRIPTION OF THE INVENTION

20

FIG. 1 is an elevational view of guidewire 10 which embodies features of the invention, and which includes an elongated core member 11 with a proximal core section 12, a distal core section 13, and a flexible body member 14 which is fixed to the distal core section. The distal core section 13 has a tapered segment 15, a flexible segment 16 which is distally contiguous to the tapered segment 15, a distal end 13a, and a proximal end 13b. The distal section 13 may also have more than one tapered segment 15 which have typical distally decreasing tapers with substantially round transverse cross sections. A guidewire having multiple continuous tapered segments in the distal section of the elongate core member is described in U.S. Patent Application Ser. No. 08/868,764, filed June 4, 1997 (Cornish, et al.) entitled STEERABLE GUIDEWIRE WITH ENHANCED DISTAL SUPPORT, which is hereby incorporated by reference in its entirety.

25

30

The core member 11 may be formed of stainless steel, NiTi alloys or combinations thereof such as described in U.S. Patent No. 5,341,818

(Abrams *et al*) which has been incorporated herein. Other materials such as the high strength alloys as described in U.S. Patent No. 5,636,641 (Fariabi), entitled HIGH STRENGTH MEMBER FOR INTRACORPOREAL USE, which is incorporated herein by reference, may also be used.

5 The core member 11 is optionally coated with a lubricious coating such as a fluoropolymer, e.g. TEFLON[®] available from DuPont, which extends the length of the proximal core section. The distal section 13 is also provided with a lubricous coating, such as a MICROGLIDE[™] coating used by the present assignee, Advanced Cardiovascular Systems, Inc. on
10 many of its commercially available guidewires. Hydrophilic coatings may also be employed.

 The length and diameter of guidewire 10 may be varied to suit the particular procedures in which it is to be used and the materials from which it is constructed. The length of the guidewire 10 generally ranges from
15 about 65 cm to about 320 cm, more typically ranging from about 160 cm to about 200 cm, and preferably from about 175 cm to about 190 cm for the coronary anatomy. The guidewire diameter generally ranges from about .008 in. to about .035 in. (.203 to .889 mm), more typically ranging from about .012 in. to about .018 in. (.305 to .547 mm), and preferably about
20 .014 in. (.336 mm) for coronary anatomy.

 The flexible segment 16 terminates in a distal end 18. Flexible body member 14, preferably a helical coil, surrounds a portion of the distal section of the elongated core 13, with a distal end 19 of the flexible body member 14 secured to the distal end 18 of the flexible segment 16 by the body of
25 solder 20. The proximal end 22 of the flexible body member 14 is similarly bonded or secured to the distal core section 13 by a body of solder 23. Materials and structures other than solder may be used to join the flexible body 14 to the distal core section 13, and the term "solder body" includes other materials such as braze, epoxy, polymer adhesives, including
30 cyanoacrylates and the like.

The wire from which the flexible body 14 is made generally has a transverse diameter of about 0.001 to about 0.004 inch, preferably about 0.002 to about 0.003 inch (0.05 mm). Multiple turns of the distal portion of coil may be expanded to provide additional flexibility. The helical coil may have a diameter or transverse dimension that is about the same as the proximal core section 12. The flexible body member 14 may have a length of about 2 to about 40 cm or more, preferably about 2 to about 10 cm in length. The flexible body member 14 may also be made from a polymer. Polymers suitable for forming a flexible body member 14 can include polyimide, polyethylene, polyurethane, TFE, PTFE, ePTFE and other similar materials. A flexible body member 14 in the form of a helical coil may be formed of a suitable radiopaque material such as platinum or alloys thereof or formed of other material such as stainless steel and coated with a radiopaque material such as gold.

The flexible segment 16 has a length typically ranging about 1 to about 12 cm, preferably about 2 to about 10 cm, although longer segments may be used. The form of taper of the flexible segment 16 provides a controlled longitudinal variation and transition in flexibility (or degree of stiffness) of the core segment. The flexible segment is contiguous with the core member 11 and is distally disposed on the distal section 13 so as to serve as a shapable member.

Referring to FIG. 2, the flexible segment 16 of guidewire 10 is shown in more detail. The flexible segment 16 is tapered distally both in height and width and has a generally square cross section defined by a first pair of opposed tapered faces and a second set of opposed tapered faces. The first set of opposed tapered faces consists of a top face 25 and a bottom face 26, which taper distally together to a smaller transverse separation. The second set of opposed tapered faces consists of a first side face 27 and a second side face 28 which taper distally together to a smaller transverse separation. Each of the tapered faces 25-28 are substantially axially coextensive and extend from the transition portion 24 of the distal section

13 to the distal end 18 of the flexible segment 16. Thus flexible segment 16 tapers to become progressively narrower in both transverse directions as the distal end 18 is approached. This results in a smooth decrease in cross sectional area and stiffness distally. Each of the tapered faces 25-28 has a longitudinal contour that is substantially straight. In addition, the top face 25 is a mirror image of the bottom face 26 about the longitudinal axis 17. The first side face 27 is a mirror image of the second side face 28 about the axis 17.

The short transition portion 24 is shaped to provide a generally continuous transition from the circular cross section of the distal end 29 of the tapered segment 15 to the substantially square cross section of the proximal end 30 of the flexible segment 16. Referring to FIG. 3, the first set of opposed tapered faces 25 and 26 are substantially normal at any given transverse cross section to the second set of opposed tapered faces 27 and 28. Or in other words, in any transverse cross section of the flexible segment 16, the lines representing the surfaces of the first set of opposed tapered faces 25 and 26 will be substantially normal to the lines representing the second set of opposed tapered faces 27 and 28.

The multiple tapers or faces of the flexible segment 16 may be ground simultaneously or as separate operations. A centerless grinder with profile capabilities may be used to grind the tapers or faces simultaneously. A manual centerless grinding may be employed to create separate tapers or faces in separate operations. Tapers or faces may also be formed by other means such as chemical means, e.g. etching, or laser means.

FIGS. 4, 5 and 6 depict an alternative embodiment of a flexible segment 40 wherein one pair of opposed tapered faces taper distally to a smaller transverse separation. This results in a smooth decrease in cross sectional area and stiffness distally over the length of the flexible segment 40. The flexible segment 40 is preferably integrally formed with a tapered segment 41 of a distal core section 42. The first opposed tapered face 43 and second opposed tapered face 44 slope distally and incline towards the

axis 45 of the segment 40. The opposed faces 43 and 44 terminate distally at the distal end 46 of the flexible segment 40. The width of the distal end 46 can be the diameter of the proximal end 47 of the flexible segment 40. In the embodiment shown, the round cross section of the tapered segment 41 is continued in the flexible segment 40 except to the extent that the material of the core 42 has been removed or shaped in order to form the first and second opposed tapered faces 43 and 44. Thus, the side surfaces 48 and 49 of the flexible segment 40 may have a curved profile. The longitudinal contours of each of the first and second opposed tapered faces are substantially straight, in addition to being mirror images about longitudinal axis 45. In FIG. 6A a transverse cross sectional view of the flexible segment 40 taken at lines 6A-6A in FIG. 5 shows the curved profile of the side surfaces 48 and 49. In addition, the flattened shape of the cross section is indicated by the major transverse dimension 49a and the short transverse dimension 49b of the flexible segment 40. In the cross section of FIG. 6A, the major transverse dimension 49a is substantially greater than the small transverse dimension 49b.

FIGS. 7, 8 and 9 depict an embodiment of a flexible segment 50 with two pairs of opposed faces which are generally coextensive in an axial direction. The first pair of opposed faces consists of a first tapered face 51 and a second tapered face 52. The second pair of opposed faces consists of a first parallel face 53 and a second parallel face 54. The first tapered face 51 and second tapered face 52 taper distally to a smaller transverse separation with respect to each other such that the distance between the first tapered face 51 and the second tapered face 52 is greater at the proximal end 55 of the flexible segment 50 than at the distal end 56 of the flexible segment.

The first parallel face 53 is substantially parallel to the second parallel face 54 along the length of the flexible segment 50 except at the proximal end 55 of the flexible segment where the first and second parallel faces terminate proximally at the first transition segment 57 and a second

transition segment 58. The optional first and second transition segments 57 and 58 span the difference in transverse dimension from the proximal end 55 of the flexible segment 50 to the distal end 61 of the tapered segment 62 of the distal core section 63. Although the first and second tapered faces 51 and 52 have substantially straight longitudinal contours, these contours may also be curved. The first and second transition segments 57 and 58 may also be curved so as to create a smooth transition at the proximal end 55 of the flexible segment 50.

While particular forms of the invention have been illustrated and described, it will be apparent that various modifications can be made without departing from the spirit and scope of the invention. Accordingly, it is not intended that the invention be limited, except as by the appended claims.

WHAT IS CLAIMED IS:

1. A guidewire comprising an elongate core member having a proximal section and a distal section with the distal section having at least one flexible segment having a smoothly distally decreasing cross sectional area and at least a portion where a major transverse dimension is substantially greater than a small transverse dimension.

2. The guidewire of claim 1 wherein the proximal section of the elongate core member has a nominally round transverse cross section and the distal section of the elongate core member further comprises a proximal end and a distal end and the flexible segment is disposed at the distal end of the distal section.

3. The guidewire of claim 2 further comprising a flexible body member having a proximal end and a distal end which is disposed about at least a portion of the distal section of the elongate core member and wherein the distal end of the flexible body member is secured to the distal end of the distal section of the elongate core member.

4. The guidewire of claim 2 wherein the flexible segment further comprises a pair of opposed tapered faces having longitudinal contours that are substantially straight.

5. The guidewire of claim 2 wherein the flexible segment further comprises a pair of opposed tapered faces having longitudinal contours that are curved.

6. The guidewire of claim 2 wherein the flexible segment further comprises a pair of opposed tapered faces having substantially mirror image longitudinal contours.

7. The guidewire of claim 2 wherein the flexible segment has a major transverse dimension that is substantially constant along its length.

8. A guidewire comprising an elongate core member having a proximal section and a distal section with the distal section having at least one flexible segment having two opposed faces tapering distally to a smaller

transverse separation and having an essentially rectangular cross sectional shape.

5 9. The guidewire of claim 8 wherein the proximal section of the elongate core member has a nominally round transverse cross section and the distal section of the elongate core member further comprises a proximal end and a distal end and the flexible segment is disposed at the distal end of the distal section.

10 10. The guidewire of claim 9 further comprising a flexible body member having a proximal end and a distal end which is disposed about at least a portion of the distal section of the elongate core member and wherein the distal end of the flexible body member is secured to the distal end of the distal section of the elongate core member.

11. The guidewire of claim 9 wherein the opposed faces have longitudinal contours that are substantially straight.

15 12. The guidewire of claim 9 wherein the opposed faces have longitudinal contours that are curved.

13. The guidewire of claim 9 wherein the opposed faces have substantially mirror image longitudinal contours.

20 14. The guidewire of claim 9 wherein the flexible segment has a major transverse dimension that is substantially constant along its length.

15. A guidewire comprising:

25 a) an elongate core member having a proximal section and a distal section with the distal section having at least one flexible segment with a first pair of opposed tapered faces tapering distally to a smaller transverse separation and a second set of opposed tapered faces which are axially coextensive with the first set of opposed tapered faces and which taper distally to a smaller transverse separation;

30 b) a flexible body member having a proximal end and a distal end disposed about at least a portion of the distal section of the elongate core member and secured to at least a portion thereof.

5

16. The guidewire of claim 15 wherein the proximal section of the elongate core member has a nominally round transverse cross section and the distal section of the elongate core member further comprises a proximal end and a distal end and the flexible segment is disposed at the distal end of the distal section.

17. The guidewire of claim 16 wherein the distal end of the flexible body member is secured to the distal end of the distal section of the elongate core member.

10

18. The guidewire of claim 16 wherein both sets of tapered faces have a longitudinal contour that is substantially straight.

19. The guidewire of claim 16 wherein both sets of tapered faces have a longitudinal contour that is curved.

20. The guidewire of claim 16 wherein a transverse cross section of any portion of the flexible segment is substantially square in shape.

15

21. The guidewire of claim 16 wherein the first set of tapered faces is substantially normal to the second set of tapered faces.

22. A guidewire comprising:

20

a) an elongate core member having a proximal section and a distal section with the distal section having at least one flexible segment with a first pair of opposed faces which taper distally to a smaller transverse separation and a second set of opposed faces which are axially coextensive with the first set of opposed faces and which are substantially parallel to each other;

25

b) a flexible body member having a proximal end and a distal end disposed about at least a portion of the distal section of the elongate core member and secured to at least a portion thereof.

30

23. The guidewire of claim 22 wherein the proximal section of the elongate core member has a nominally round transverse cross section and the distal section of the elongate core member further comprises a proximal end and a distal end and the flexible segment is disposed at the distal end of the distal section.

24. The guidewire of claim 23 wherein the distal end of the flexible body member is secured to the distal end of the distal section of the elongate core member.

5 25. The guidewire of claim 23 wherein the first set of opposed faces and the second set of opposed faces have a longitudinal contour that is substantially straight.

26. The guidewire of claim 23 wherein the first set of opposed faces and the second set of opposed faces have a longitudinal contour that is curved.

10 27. The guidewire of claim 23 wherein the second set of opposed faces have a transverse dimension greater than a transverse dimension of the first set of opposed faces along a substantial length of the flexible segment.

15 28. The guidewire of claim 23 wherein a transverse cross section of any portion of the flexible segment is substantially rectangular in shape.

29. The guidewire of claim 23 wherein the first set of opposed faces is substantially normal to the second set of opposed faces.

1/3




FIG. 1




FIG. 2








FIG. 3






FIG. 7




FIG. 8




FIG. 9

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/30771A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61M25/09

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 003 369 A (HEILMAN ET AL.) 18 January 1977 (1977-01-18) abstract; figures 4B-5F	8-14
A	US 5 497 783 A (PRATHER ET AL.) 12 March 1996 (1996-03-12) abstract; figures 1,3A,B	1-21
A	US 4 854 330 A (EVANS ET AL.) 8 August 1989 (1989-08-08) abstract; figures 2,6-8	1-29
A	WO 97 24978 A (INTELLA INTERVENTIONAL SYSTEMS, INC.) 17 July 1997 (1997-07-17) abstract; figures 29-32	22-29
	-/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

3 May 2000

Date of mailing of the international search report

12/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Michels, N

INTERNATIONAL SEARCH REPORT

Int'l. Application No
PCT/US 99/30771

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category.*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 3 452 742 A (MULLER WOLF F) 1 July 1969 (1969-07-01)</p> <p>figure 6</p>	<p>1,5,8, 12,15, 19,22,26</p>

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter. Application No.

PCT/US 99/30771

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4003369	A	18-01-1977	US 4080706 A	28-03-1978
US 5497783	A	12-03-1996	US 5666969 A	16-09-1997
US 4854330	A	08-08-1989	NONE	
WO 9724978	A	17-07-1997	US 5697380 A	16-12-1997
			US 5813997 A	29-09-1998
			US 5938623 A	17-08-1999
			AU 1531597 A	01-08-1997
			US 6039743 A	21-03-2000
US 3452742	A	01-07-1969	DE 1491851 A	16-04-1970
			GB 1119159 A	
			SE 345592 B	05-06-1972

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.